

SPOT LEVEL SELF-SEALING SAMPLERS (CAGE SAMPLERS)



Cage samplers can be used to draw liquid samples from any depth of a tank or reservoir.

The sampler is kept upright during the descent, which also protects the glass bottle from breakage. The sampler is sealed until the operator opens the top valve.



These samplers are suited to taking samples for quality, density, RVP, and appearance

A polypropylene ball is used to reseal the sampler's opening. The self-sealing functionality of the sampler reduces the amount of liquid that leaks out when it is opened.



* These samplers can be modified to accommodate customers' preferred bottle types.

Model	Capacity	Length	Diameter	Material	Sampling height from bottom	Bottle Protection	Weight
ALSB 1/3/16	16 OZ	36 cm	76 mm	Brass	30 cm	Metal Sleeve	1.6 kg
ALSB 2/3/16	16 OZ	36 cm	76 mm	Stainless Steel	30 cm	Metal Sleeve	1.6 kg
ALSB 1/4/16	16 OZ	38 cm	102 mm	Brass	32 cm	Swivelling Cage	1.5 Kg
ALSB 2/4/16	16 OZ	38 cm	102 mm	Stainless Steel	32 cm	Swivelling Cage	1.5 Kg
ALSB 1/4/5	16 OZ / 500 ml	39 cm	120 mm	Brass	33 cm	Swivelling Cage	1.7Kg
ALSB 2/4/5	16 OZ / 500 ml	39 cm	120 mm	Stainless Steel	33 cm	Swivelling Cage	1.7Kg
ALSB 1/1L	16 OZ / 1 ltr	42 cm	132 mm	Brass	36 cm	Swivelling Cage	2.0 Kg
ALSB 2/1L	16 OZ / 1 ltr	42 cm	132 mm	Stainless Steel	36 cm	Swivelling Cage	2.0 kg
ALSC 1002	1 ltr	42 cm	76 mm	Stainless Steel	36 cm	Metal Canister	3.0 kg
ALSC 2/1L/64	1 ltr	55 cm	64 mm	Stainless Steel	49 cm	Metal Canister	2.0 Kg